


Logico Suspension - White



IP20 🔔 🛞 🕅 🖻 🚳 Dimmerable: +0-

TECHNICAL DRAWINGS



DESIGN BY

Gerhard Reichert, Michele De Lucchi

Article Code:	0453020A	Material:	Blown glass,
Colour:	White		aluminium
Installation:	Suspension	Series:	Design
Environment:	Indoor	Area contract:	Hospitality, Office
		Emission:	Diffused And Direc
DIMENSIONS			
Width:	cm 40		
Height:	cm 31		
Base Diameter:	cm 18		
Max Height from ceiling:	cm 200		
NOT INCLUDED SOUR	CES		
Category:	HALO	Color temperature (K):	2700K
Number:	1	Class:	А
Watt:	116W		
Socket:	E27		
ALTERNATIVE SOURCE	S		
Category:	LED		
Number:	1		
Watt:	15W		
Туре:	2		
Socket:	E27		
Class:	А		
LUMINAIRE			
	W	Delivered lumens output (lm):1639lm	
Watt:	VV		
Watt: Voltage:	vv 220V-240V	сст:	2800K
		CCT:	2800K

Notes

Available in four sizes and in four configurations: single, on line, 3x120° and 4x90°. Its modular shape lends itself to the creation and realisation of customized compositions, supplied as special project. Logico nano track is available with track adapter.




Logico Ceiling - White



IP20 🗆 🛞 🕅 🞯 🚳 Dimmerable: +0-

TECHNICAL DRAWINGS



DESIGN BY

Gerhard Reichert, Michele De Lucchi

Article Code:	0452020A	Material:	Blown glass,
Colour:	White		aluminium
Installation:	Ceiling	Series:	Design
Environment:	Indoor	Area contract:	Hospitality, Office
		Emission:	Diffused And Direc
DIMENSIONS			
Length:	cm 40		
Width:	cm 40		
Height:	cm 32.5		
NOT INCLUDED SO	OURCES		
Category:	HALO	Color Rendering:	1a
Number:	1	Color temperature (K):	2900K
Watt:	116W	•	
Lbs:	Qa60		
Socket:	E27		
ALTERNATIVE SOL	JRCES		
Category:	LED		
Number:	1		
Watt:	15W		
Туре:	2		
Socket:	E27		
Class:	А		
LUMINAIRE			
Watt:	W	Delivered lumens output (lm):1639lm	
Voltage:	220V-240V	сст:	2800K
		Efficiency:	86%
		-	
		Efficacy:	15.61lm/W

<u>Notes</u>

Its modular shape lends itself to the creation and realisation of customized compositions, supplied as special project.