

HENGE[®]

Certified Product
Prodotto certificato



Product Sheet

Model

TUBULAR HORIZONTAL . CEILING

Dimmable energy saving led Pendant light, GU10 (energy efficiency index A) 15,3W 350Lumen 3000Kelvin leds pointing upward and downward, body Ø 7 cm and Ø 10 cm
FINISH Brass hand-burnished using traditional techniques.

Scheda Prodotto

Modello


TUBULAR HORIZONTAL . A SOSPENSIONE

Lampada a sospensione a led dimmerabile, (classe energetica tipo A) aggancio GU10 5,3W 350Lumen 3000Kelvin, led rivolti verso l'alto e verso il basso consumo. **FINITURA** Ottone brunito a mano secondo le tecniche tradizionali.


TUBULAR HORIZONTAL

Design Massimo Castagna


Tubular Horizontal 70
Cylinder diameter .
Diametro cilindro Ø 7 cm




Tubular Horizontal 70
Cylinder diameter .
Diametro cilindro Ø 10 cm




Tubular Horizontal 100
Cylinder diameter .
Diametro cilindro Ø 7 cm




Tubular Horizontal 100
Cylinder diameter .
Diametro cilindro Ø 10 cm



Tubular Horizontal 150
Cylinder diameter .
Diametro cilindro Ø 7 cm



Tubular Horizontal 150
Cylinder diameter .
Diametro cilindro Ø 10 cm



DIMENSIONS

L. 70 cm; Ø 7 cm;
4x5,3W 350Lm 3000K
L. 100 cm; Ø 7 cm;
4x5,3W 350Lm 3000K
L. 150 cm; Ø 7 cm;
4x5,3W 350Lm 3000K
L. 70 cm; Ø 10 cm;
4x5,3W 350Lm 3000K
L. 100 cm; Ø 10 cm;
4x5,3W 350Lm 3000K
L. 150 cm; Ø 10 cm;
4x5,3W 350Lm 3000K

DIMENSIONI

L. 70 cm; Ø 7 cm;
4x5,3W 350Lm 3000K
L. 100 cm; Ø 7 cm;
4x5,3W 350Lm 3000K
L. 150 cm; Ø 7 cm;
4x5,3W 350Lm 3000K
L. 70 cm; Ø 10 cm;
4x5,3W 350Lm 3000K
L. 100 cm; Ø 10 cm;
4x5,3W 350Lm 3000K
L. 150 cm; Ø 10 cm;
4x5,3W 350Lm 3000K